

NW1030F

Non-refined Polyethylene Homopolymer Wax

Special Characteristics : The product is a polyethylene homopolymer wax produced using a high density polyethylene (HDPE) technology.

Typical Applications : Calcium carbonate and color masterbatches, PVC, Hot melt adhesives, and Thermoplastics road markings, etc.

Typical Properties :

Properties	NW1030F	Unit	Test Method
Physical Properties			
Product form	Flake	-	-
Viscosity (149 °C)	100 - 300	cPs	ASTM D3236
Dropping point	116	°C	ASTM D3954
Penetration index	> 3	d.mm	ASTM D1321

Disclaimer: To the best of our knowledge, the information contained herein is accurate and reliable as of the date of publication; however, we do not assume any liability what so ever for the accuracy and completeness of such information. We make no warranties which extend beyond the description contained herein. Nothing herein shall constitute any implied warranty of merchantability or fitness for a particular purpose. It is the customer's responsibility to inspect and test our products in order to satisfy itself as to the suitability of the products for the customer's particular purpose. The customer is responsible for the appropriate, safe and legal use, processing and handling of our products. No liability can be accepted in respect of the use of our products in conjunction with other materials. The information contained herein relates exclusively to our products when not used in conjunction with any third party materials.

Note : Properties reported here are typical values of the product, not to be considered as specifications.

GC makes no representations as to the accuracy or completeness of the information contained herein.