

Safety Data Sheet

Section 1. Chemical Product and Company Identification			
Product name	DIAREX GPPS	In Case of Emergency and Technical Information	Thailand: +66(0)-3897-6682 +66(0)-3897-6683 +66(0)-3897-6684
Synonym	General Purpose Polystyrene, Vinylbenzene polymer, Styrene polymer	Revision	Feb 2024
		Product Grade	TMF35
Chemical Family	Ethenylbenzene homopolymer		
CAS Registry Number	9003-53-6	SDS No.	PS0001 (EN)
Company Name / Manufacturer Address	PTT Global Chemical Public Company Limited 7, I-1 Road, Maptaput Industrial Estate, Map Ta Phut, Muang Rayong District, Rayong 21150, Thailand,		

Section 2. Hazards Identification

Emergency Overview	Irritating vapors to respiratory system and eyes may form when polymer is processed at high temperatures.
Routes of Entry Potential Acute Health Effects	Molten or heated material in skin contact can cause severe burns. FOR HOT MATERIAL: Skin contact. Eye contact. Inhalation.
Eyes	Dust may cause mechanical irritation to eye. Heated Polymer: Eye contact can cause serious thermal burns. Vapors formed when polymer is heated may be irritating to the eye.
Skin	No known acute effects of this product resulting from skin contact at room temperature. Heated Polymer: skin contact can cause serious thermal burns.
	Negligible at room temperature. Nuisance dusts can be irritating to the upper respiratory tract.Irritating vapors may form when the polymer is processed at high temperatures. No effects are expected for ingestion of small amounts. May be a choking hazard.
Potential Chronic Health Effects	CARCINOGENIC EFFECTS: Polystyrene is not a known carcinogen. Not listed as a carcinogen by OSHA, NTP or IARC.
Medical Conditions Aggravated by Overexposure	Pre-existing disorders involving any target organs mentioned in this SDS as being at risk may be aggravated by over-exposure to this product.
Overexposure/Signs/ Symptoms	No adverse health effects anticipated from the solid pellet.





Section 3. Composition and Information on Ingredients

Substance Name	CAS No.	<u>% by Weight</u>
Polystyrene	9003-53-6	> 96.75
Additives	-	< 3.25

Section 4. First Aid Measures

Eye Contact Skin Contact	Rinse with water for a few minutes. Seek medical attention if necessary Polymer: NO known EFFECT on skin contact, rinse with water for few minutes. Heated Polymer: For serious burns from heated polymer, get medical attention. In case of skin contact, immediately immerse in or flush with clean, cold water.
Inhalation	Non-toxic material. Dusts in high concentrations may cause irritation to upper respiratory tract. Allow the victim to rest in a well-ventilated area.
Ingestion	Not expected that the ingestion of this material causes an effect on health. The toxicity of a single oral dose in considered. extremely low.

Section 5. Fire Fighting Measures

Flammability of the Product Auto-ignition Temperature	May be combustible at high temperature. 488 – 496 º C.
Flash Points	>550 0 C . 296 – 360 0 C (under condition of decomposition excess heating decompose polystyrene and decomposed materials makes flash point lower.
Flammable Limits	Not available.
Products of Combustion	Canproduce carbon monoxide (CO), carbon dioxides (CO2), styrene, aliphatic hydrocarbons and soot.
Fire Hazards in Presence of Various Substances	No specific information is available in our database regarding the flammability of this product in presence of various materials.
Fire Fighting Media and Instructions	SMALL FIRE: Dry chemical extinguisher (ABC or AB). Use water spray or fog. LARGE FIRE: Use water spray or fog. Do not use water jet.
Protective Clothing (Fire)	May re-ignite itself after fire is extinguished Wear MSHA/NIOSH-approved self-contained breathing apparatus or equivalent and full protective gear.
Special Remarks on Fire Hazards	Fire may produce irritating gases and dense smoke. Flowing material may produce static discharge, igniting dust accumulations.
Special Remarks on Explosion Hazards	Processing or material handling equipment may generate dust of sufficiently small particle size, that when suspended in air may be explosive.

บริษัท พีที่ที่ โกลบอล เคมิคอล จำกัด (มหาชน) 555/1 ศูนย์เอนเนอร์ยี่คอมเพล็กซ์ อาคารเอ ชั้น 18 ถนนวิภาวดีรังสิด แขวงจตุจักร เขดจดุจักร กรุงเทพฯ 10900 โทร+66-2265-8400 โทรสาร +66-2265-8500



Section 6. Accidental Release Measures

Small Spill and Leak	Pellets on the floor could present a serious slipping problem. Good housekeeping must be maintained at all times to avoid this hazard. Sweep, shovel, or vacuum material into clean containers.
Large Spill and Leak	Use a shovel to put the material into a convenient waste disposal container. Do not allow any potentially contaminated water with pellets to enter any waterway, sewer or drain.
	any potentially containinated water with penets to effer any waterway, sewer or drain.

Section 7. Handling and Storage

Handling	Avoid Temperatures of 600°F (316°C) or above.
	Handling of plastic may form nuisance dust. Protect personnel.
	Pneumatic material handling and processing equipment may generate dust of sufficiently small particle size that, when suspended in air, may be explosive. Dust accumulations should be controlled through a comprehensive dust control program that includes, but is not limited to, source capture, inspection and repair of leaking equipment, routine housekeeping and employee training in hazards. See NFPA 654.
	Dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material.
	When handled in bulk quantities, this product and its associated packaging may present a crushing hazard due to the large masses involved, possibly resulting in severe injury or death.
Storage	Keep container dry. Keep in a cool place. Ground all equipment containing material. Keep container tightly closed. Keep in a cool, well-ventilated place. Combustible materials should be stored away from extreme heat and away from strong oxidizing agents.

Section 8. Exposure Controls/Personal Protection

Control Parameter Exposure limit value	Occupational Exposure limit (OEL) GESTIS-International limit values for chemical agents
Engineering Controls	Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below established levels. If user operations generate dust, fumes or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit.
Personal Protection	
Eyes	Safety glasses with side shields.
Body	Coveralls.
Respiratory	Ventilation is normally required when handling this product at high temperatures. Wear appropriate respirator when ventilation is inadequate.
Hands	Thermally insulated gloves required when handling hot material.
Feet	Shoes.
Protective Clothing (Pictograms)	

Disclaimer: To the best of our knowledge, the information contained herein is accurate and reliable as of the date of publication; however, we do not assume any liability what so ever for the accuracy and completeness of such information. We make no warranties which extend beyond the description contained herein. Nothing herein shall constitute any implied warranty of merchantability or fitness for a particular purpose. It is the customer's responsibility to inspect and test our products in order to satisfy itself as to the suitability of the products for the customer's particular purpose. The customer is responsible for the appropriate, safe and legal use, processing and handling of our products. No liability can be accepted in respect of the use of our products in conjunction with other materials. The information contained herein relates exclusively to our products when not used in conjunction with any third party materials.

For more information and technical assistance contact; PTT Global Chemical Public Company Limited 555/1, Energy Complex, Building A, 18th Floor, Vibhavadi Rangsit Road, Chatuchak, Chatuchak, Bangkok 10900 TEL+66-2265-8400 Fax +66-2265-8500

บริษัท พีทีที่ โกลบอล เคมิคอล จำกัด (มหาชน) 555/1 ศูนย์เอนเนอร์ยี่คอมเพล็กซ์ อาคารเอ ชั้น 18 ถนนวิภาวดีรังสิด แขวงจดจักร เขดจดจักร กรุงเทพฯ 10900 โทร+66-2265-8400 โทรสาร +66-2265-8500



Personal Protection in Case of a Large Spill

Safety glasses. Gloves. Coveralls

Exposure Limits Not established.

Product Name

Polystyrene (GPPS)

Consult local authorities for acceptable exposure limits.

Section 9. Physical and Chemical Properties

9.1. General Information (appearance, odor)	
Physical State and Appearance	Solid. Pellets.
Color	Clear with Slightly Blue
Odor	Odorless.
Oder Threshold	Not available.
9.2. Important Health, Safety and Environme	ental Information
Flash Point	>550 °C.
	$296 - 360^{\circ}$ C (under condition of decomposition excess heating decompose
Flammability (solid,gas) Flammable Limited in Air	polystyrene and decomposed materials makes flash point lower. Not applicable. Lower ; Not applicable. Upper ; Not applicable
Auto ignition Temperature Vapor Pressure Boiling Point (760 mmHg) VOC	488 – 496 [°] C. Not applicable. Not applicable. 0 (%)
Solubility	Insoluble in water. Soluble in esters, ketone, aromatic hydrocarbons.
Volatility	Negligible.
Decomposition Temperature 9.3. Other data	Equilibrium point between polymerization and de-polymerization is around 250 °C.
Molecular Weight Molecular Formula Melting Point Specific Gravity Freezing Point	Not applicable. (-CH(C6H5)-CH2-)x > 132 °C 1.05 (Water = 1) Not applicable

Section 10. Stability and Reactivity

Reactivity	No information available.
Stability	This product is stable under normal conditions.
Hazardous Polymerization	Under normal conditions of storage and use, hazardous polymerization will not occur
Conditions to Avoid Incompatibility with Various Substances	Keep away from heat, flames and sparks. Avoid Temperatures of 600°F (316°C) or above. Reactive with strong oxidizing agents.
Hazardous Decomposition Products	Hazardous decomposition products are carbon monoxide, carbon dioxide, dense smoke, and various hydrocarbons. Exposure of polystyrene to extremely high temperatures (600 deg F or higher) may cause partial decomposition. Chemicals that may be released include styrene monomer, benzene, and other hydrocarbons.

บริษัท พีที่ที่ โกลบอล เคมิคอล จำกัด (มหาชน) 555/1 ศูนย์เอนเนอร์ยี่คอมเพล็กซ์ อาคารเอ ชั้น 18 ถนนริภาวดีรังสิด แขวงจตุจักร เขดจดุจักร กรุงเทพฯ 10900 โทร+66-2265-8400 โทรสาร +66-2265-8500



Section 11. Toxicological Information

Acute Toxicity	
Ingestion	Single dose oral LD50 has not been determined. Typical for this family of materials, estimated. LD50,Rat > 5,000 mg/kg
Dermal	The dermal LD50 has not been determined. Typical for this family of materials, estimated.
	LD50,Rabbit > 2,000 mg/kg.
Inhalation	The LD50 has not been determined.
Eye damage / Irritation	Solid or dust may cause irritation or corneal injury due to mechanical action. Elevated temperature may generate vapor levels sufficient to cause eye irritation. Effects may include discomfort and redness.
Skin corrosion / irritation	Prolonged contact is essentially nonirritating to skin. Mechanical injury only. Under normal
	processing conditions, material is heated to elevated temperatures, contact with the material may
	cause thermal burns.
Sensitization	
Skin	No relevant information found.
Respiratory	No relevant information found.
Repeated Dose Toxicity	Additives are encapsulated in the product and are not expected to be released under normal Processing conditions or foreseeable emergency.
Chronic Toxicity and Carcinogenicity	No relevant information found.
Development Toxicity	No relevant information found.
Reproductive Toxicity	No relevant information found.
Reproductive Toxicity	

Section 12. Ecological Information

Ecotoxicity Persistence and degradability	This product is essentially a high molecular weight polymer, not regarded as ecotoxic . This product is not readily biodegradable. Persistent in the environment.
Bioaccumulation	May accumulate in soil and water systems.
Fire Hazards in Presence of Various Substances	No specific information is available in our database regarding the flammability of this product in presence of various materials.
Explosion Hazards in Presence of Various Substances	Risks of explosion of the product in presence of mechanical impact: Not expected. Risks of explosion of the product in presence of static discharge: Possible. Risk of explosion from dust accumulation of this product is possible. See MSDS section 7 Handling for more information.



Section 13. Disposal Considerations

Description and handling Of residues	The same safety consideration apply to scrups / waste as apply to the preparation.
Appropriate methods of Disposal of preparation	Residues should be disposed of as required by national and local regulations.
Incineration	Must be done under approved conditions, possibly with energy recovery and only at suitable facilities equipped with a scrubber for the treatment of fumes before their release into the atmosphere.
Recycling	After suitable treatment (cleaning, grinding, etc.), the preparation can be safety re-used, as is or mixed with fresh material, when this is compatible with the intended final application.
Landfilling National and Community provisions relating Waste Information	Should be avoided as far as possible. If unavoidable , use approved landfill sites. Directive 91/156/EEC of 18 March 1991; Directive 91/189/EEC of 12 December 1991; Directive 91/62/EEC of 20 December 1994.
Consult your local or regional authorities.	Transfer to an approved disposal area in accordance with federal, state, and local regulations.

Section 14. Transport Information

IMDG		
Proper Shipping Name	Not regulated. Not regulated.	
Hazard class		
UN Number	Not regulated.	
Packing Group	Not regulated.	
Special Provisions	None.	
Marine Pollutant	Not applicable	
Environmental hazard		
RID		
Proper Shipping Name	Not regulated	
Hazard class	Not regulated	
UN Number	Not regulated	
Packing Group	Not regulated	
Special Provisions	None	
Environmental hazard	Not applicable	
ADR		
Proper Shipping Name	Not regulated	
Hazard class	Not regulated	
UN Number	Not regulated	
Packing Group	Not regulated	
sclaimer: To the best of our knowledge, the information of	contained herein is accurate and reliable a	

บริษัท พีทีที่ โกลบอล เคมิคอล จำกัด (มหาชน) 555/1 ศูนย์เอนเนอร์ยิคอมเพล็กซ์ อาคารเอ ชั้น 18 ถนนวิภาวดีรังสิด แขวงจดุจักร เขดจดุจักร กรุงเทพฯ 10900 โทร+66-2265-8400 โทรสาร +66-2265-8500



Special Provisions Environmental hazard None Not applicable

Section 15. Regulatory Information

Thailand : Hazardous Substance Act,B.E.2535	This product does not contain substances listed in Thai Hazardous substances Act.	
Thailand : Notification of Ministry of Interior (Occupational Health and Safety in Chemical)	All components of this product are not listed.	
HCS Classification	This product is not a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.	
International Regulations DSCL (EEC)	This product is not classified according to EU legislation	
International List	Australia inventory (AICS): This material is listed or exempted. China inventory (IECSC): This material is listed or exempted. Japan inventory (ENCS): This material is listed or exempted. Japan inventory (ISHL): Not determined. Korea inventory (KECI): This material is listed or exempted.	
DISCLAIMER	 This Applications specified herein is for reference only and not suitable for using in the manufacturing of any products in medical and pharmaceutical sectors. Determination of suitability of the product for the use and purpose shall be the customer's responsibility. Customer is obligated to inspect and test the product for such suitability. Customer is responsible for appropriate, safe, legal use processing and handling of the product. To our best knowledge, information contained herein is true and accurate as of the date of its publication. However, we make no representations or warranties with respect to accuracy, reliability and completeness of the information contained herein for any purpose. No warranties, express or implied, which extend beyond the description herein are given by us. Nothing herein shall constitute any implied warranty of merchantability or fitness for a particular purpose. We assume no liability for any use of the product in combination with other materials. The information contained herein entirely relates to the product when it is not used in combination with any third party's materials. 	

Section 16. Other Information

Product Literature

Additional information on this product may be obtained by calling your sales or customer service contact.